



#2193

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: #2193 HIGH PERFORMANCE, UNI-DIRECTIONAL GLASS REINFORCED FILM STRAPPING TAPE

DESCRIPTION: Fiberglass strand reinforced, film backed, rubber based pressure sensitive strapping tape with medium strength and good adhesion. Designed for most utility grade applications.

SPECIFICATION:

Backing	1 mil Polypropylene	
Adhesion to Steel	90 oz./in. width	98 N/100 mm
Adhesion to Kraft	33 oz./in. width	36 N/100 mm
Tensile Strength	130 lbs./in. width	2275 N/100 mm
% Elongation	4.0%	
Total Thickness	5.2 mils	0.132 mm
Temperature Resistance	Good	
Holding Power	Excellent	
Stain Resistance	Good	
Color	White	

Features:	Benefits:
Unique Lamination Procedure	Low Cost / High Strength
High Performance Hot Melt Adhesive	Positive strand bond to backing, no strand delamination
	Excellent tack & quick stick
	High adhesion to Kraft – good fiber tear
	Good temperature range - 32°F to 170°F
	Clean removal for most glass and metal surfaces
	Non-staining

P
R
O
D
U
C
T

D
A
T
A

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.