



#2225

250 Canal Road, Fairless Hills, PA 19030  
P: (215) 736-3644 or (800) 366-8272  
F: (215) 428-4510

PRODUCT: **#2225 TENSILIZED POLYPROPYLENE FILM**

DESCRIPTION: Solvent-free acrylic adhesive combined with a super-strong copolymer resin makes this product an ideal choice for corrugators that demand top quality features for their customers. This product is excellent for use as a tear open mechanism for other packaging materials including shrink wrap, tamper-resistant overwraps, foils, multi-wall paper chipboard and plastic mailing bags.

SPECIFICATION:

Backing	Cast-extruded and Tensilized Monoaxially-Oriented Polypropylene Film	
Adhesion to Steel	25 oz./in. width	27 N/100 mm
Tensile Strength	150 lbs./in. width	2625 N/100 mm
% Elongation	30.0%	
Total Thickness	4.0 mils	0.124 mm
Color	Ivory, Red, Transparent and White	

P  
R  
O  
D  
U  
C  
T  
  
D  
A  
T  
A

**Important Notice To Buyer:** All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.