



#222 TPP

250 Canal Road, Fairless Hills, PA 19030  
P: (215) 736-3644 or (800) 366-8272  
F: (215) 428-4510

**PRODUCT: #222 TPP HEAVY-DUTY TENSILIZED STRAPPING TAPE WITH CLEAN REMOVAL RUBBER BASED ADHESIVE**

**DESCRIPTION:** Specialty grade TPP with high tensile strength and low elongation is combined with an aggressive, high shear, hot melt adhesive. Ideal for coil tabbing, L-clip, and appliance applications with excellent resistance to stretching. Leaves no residue upon removal.

**SPECIFICATION:**

Backing	Monoaxially-oriented Polypropylene Film	
Adhesion to Steel	75 oz./in. width	82 N/100mm
Tensile Strength	150 lbs./in. width	2625 N/100mm
% Elongation	15%	
Total Thickness	5.5 mils	0.140 mm
Color	Blue	

**P  
R  
O  
D  
U  
C  
T  
  
D  
A  
T  
A**

**Features:**

P.P. Film  
Low Elongation  
High Performance Rubber Adhesive

**Benefits:**

Low Cost / High Strength  
Tight secure bundling with limited stretching  
Aggressive high shear adhesive with clean removal

**Important Notice To Buyer:** All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.