



#35 OPP

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: #35 OPP GENERAL PURPOSE ACRYLIC CARTON SEALING TAPE

DESCRIPTION: A highly transparent, long lasting adhesive combined with polypropylene film designed primarily for top and bottom sealing of regular slotted containers (RSC's). Good resistance to water, temperature extremes, solvents, and ultraviolet light makes this an excellent tape for most box sealing applications.

SPECIFICATION:

Backing	Biaxially - Oriented Polypropylene Film	
Adhesion to Steel	19-oz./in. width	21 N/100mm
Tensile Strength	19 lbs./in. width	333 N/100mm
% Elongation	140%	
Total Thickness	1.7 mils	0.043 mm
Color	Clear	

Features: Biaxially Oriented Polypropylene Film Acrylic Adhesive	Benefits: Clear, strong cost effective, protects from moisture & solvents Excellent UV resistance, great aging, won't yellow, performs well in wide range of temperatures Application Temp. 32° to 140° F Operation Temp -10°to 200° F
---	---

P
R
O
D
U
C
T

D
A
T
A

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.