



#38 OPP

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: #38 OPP PRODUCTION GRADE ACRYLIC CARTON SEALING TAPE

DESCRIPTION: A highly transparent, long lasting, acrylic adhesive combined with a heavy gauge polypropylene film makes this product ideal for automatic carton closing applications. Its steady consistent unwind insures accurate, fast dispensing, while its high strength resists edge tear and splitting due to impact shock.

SPECIFICATION:

Backing	Biaxially - Oriented Polypropylene Film	
Adhesion to Steel	23-oz./in. width	25 N/100mm
Tensile Strength	26 lbs./in. width	455 N/100mm
% Elongation	140%	
Total Thickness	1.9 mils	0.048 mm
Color	Clear, Tan	

Features: Biaxially Oriented Polypropylene Film Acrylic Adhesive	Benefits: Clear, strong cost effective, protects from moisture & solvents Excellent UV resistance, great aging, won't yellow, performs well in wide range of temperatures Application Temp. 32° to 140° F Operation Temp -10°to 200° F
---	---

P
R
O
D
U
C
T

D
A
T
A

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.