



#53 HP

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: **#53 HP HOT MELT CARTON SEALING TAPE**

DESCRIPTION: Tough, heavy-duty, high performance rubber based adhesive combined with a heavy gauge polypropylene film makes this product ideal for automatic carton closing, high sheer applications.

SPECIFICATION:

| | | |
|-------------------|---|-------------|
| Backing | 30 Micron Biaxially - Oriented Polypropylene Film | |
| Adhesion to Steel | 40-oz./in. width | 44 N/100mm |
| Tensile Strength | 25 lbs./in. width | 438 N/100mm |
| % Elongation | 135% | |
| Total Thickness | 2.2 mils | 0.056 mm |
| Color | Clear, Print, White | |

Note: The above data should be considered representative or typical only. Should not be used for specification purposes.

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.

Update 8/14/06 Supersedes 01/14/05

P
R
O
D
U
C
T

D
A
T
A