



#58

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: #58 PRODUCTION GRADE HOT MELT CARTON SEALING TAPE

DESCRIPTION: This is a production grade hot melt rubber based adhesive product, designed for use in most carton closing applications, manual or automatic.

SPECIFICATION:

Backing	28 Micron Biaxially - Oriented Polypropylene Film	
Adhesion to Steel	48 oz./in. width	52 N/100mm
Tensile Strength	22 lbs./in. width	385 N/100mm
% Elongation	110%	
Total Thickness	1.8 mils	0.046 mm
Color	Clear	

Note: The above data should be considered representative or typical only. Should not be used for specification purposes.

P
R
O
D
U
C
T

D
A
T
A

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.