



#65 OPP

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: #65 OPP HIGH PERFORMANCE GRADE, HEAVY DUTY, ACRYLIC CARTON SEALING TAPE

DESCRIPTION: A highly transparent, long lasting, acrylic adhesive combined with tough heavy gauge, high heavy-duty polypropylene film. This product is ideal for automatic carton closing applications. Its steady, consistent, unwind insures accurate and fast dispensing while its high-strength resists edge tear and splitting due to impact shocks in rough handling applications

SPECIFICATION:

Backing	Biaxially-Oriented Polypropylene Film	
Adhesion to Steel	31-oz./in. width	34 N/100mm
Tensile Strength	34 lbs./in. width	595 N/100mm
% Elongation	130%	
Total Thickness	2.7 mils	0.069 mm
Color	Clear	

Features: Heavy Duty Biaxially-Oriented Film Heavy Duty Acrylic Adhesive Range of Temperatures	Benefits: Clear and extra strong, great for tough applications, resists moisture & solvents Aggressive adhesive for high stress applications when clear, non-yellow appearance is important Excellent UV resistance, moisture resistant with great aging properties Application Temp – 32° to 140° F Operation Temp –10°to 200° F
--	---

P
R
O
D
U
C
T

D
A
T
A

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.