



#84

250 Canal Road, Fairless Hills, PA 19030
P: (215) 736-3644 or (800) 366-8272
F: (215) 428-4510

PRODUCT: #84 SELF-WOUND OVERLAMINATE FILM

DESCRIPTION: Super duty acrylic coated PET self wound overlamination film.

SPECIFICATION:

Backing	Polyester Film	
Adhesion to Steel	20-oz./in. width	22 N/100mm
Tensile Strength	25 lbs./in. width	438 N/100mm
% Elongation	110%	
Total Thickness	1.3 mils	0.033 mm

**P
R
O
D
U
C
T

D
A
T
A**

<u>Features:</u> Polyester Film	<u>Benefits:</u> Great clarity Resists abrasion, moisture and solvents
---	---

Important Notice To Buyer: All statements, information and recommendations contained herein are based on calculations and tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.